


产品描述

- 额定温度: 105° C
- 额定电压: 300V
- 导体: 单支或绞合 36~14AWG 镀锡或裸铜
- 绝缘: 聚氯乙烯 (PVC)
- 阻燃等级: VW-1及CSAFT1、FT2
- 参考标准: UL758 UL1581 UL2556
- 适用范围:
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rate temperature: 105° C
- Rate voltage: 300V
- Conductor: 36~14AWG (Solid or stranded, tinned or bare copper)
- Insulation: PVC
- Flame test: VW-1&CSAFT1、FT2
- Reference standard: UL758 UL1581 UL2556
- Application: For internal wiring of electronic and electrical equipment



印字 MARKING

AWM 2651 ()AWG 105° C 300V VW-1 E332441 YA0BO cUL AWM I A 105° C 300V FT1

产品结构 CABLE CONSTRUCTION



导体 CONDUCTOR					绝缘 INSULATION		最大导体电阻 MAX. COND. RESISTANCE (Ω /km, 20℃, DC)	标准长度 STANDARD PUT-UP	
规格 AWG	间距 Pitch (mm)	构造 CONSTRUCTION (No. /mm)	外径 DIA. (mm)	芯数 (No)	厚度 THICKNESS (mm)	外径 OD (mm)		英制 Ft/Ro11	公制 M/Ro11
30	1.27	7/0.1	0.30	2-64	0.26	0.85	376.96	250	76.2
28	1.27	7/0.127	0.39	2-64	0.26	0.90	237.25	250	76.2
26	1.27	7/0.16	0.49	2-64	0.26	1.0	148.94	250	76.2
24	1.27	11/0.16	0.61	2-64	0.30	1.2	93.25	250	76.2